

Safety Data Sheet

Revision Date: 13-Jul-2018

Version 1

1. IDENTIFICATION

Product Identifier Product Name	Fuel Treatment FT-10™
Other means of identification SDS #	MP-016
UN/ID No	UN1993
Recommended use of the chemical	and restrictions on use
Recommended Use	Gasoline or diesel fuel additive.
Details of the supplier of the safety Manufacturer Address Muscle Products Corp 752 Kilgore Road Jackson Center, PA 16133 www.musclelubricants.com	<u>data sheet</u>
Emergency Telephone Number Company Phone Number Emergency Telephone (24 hr)	1-814-786-0166 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)
	2. HAZARDS IDENTIFICATION

Appearance Dark green (may be special blended to dark red) liquid

Physical state Liquid

Odor Alcohol-type

Classification

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

Signal Word Danger

Hazard statements

Causes serious eye irritation Suspected of causing cancer May cause drowsiness or dizziness May be fatal if swallowed and enters airways Highly flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower IF INHALED: Remove person to fresh air and keep comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting IN CASE OF FIRE: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Isopropyl Alcohol	67-63-0	60-70
Kerosene	8008-20-6	20-30
Naphtha (petroleum), heavy aromatic	64742-94-5	0.6-1.15
Naphthalene	91-20-3	<5
Proprietary Organic Compound	Proprietary	1-5
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	0.2-0.4
Ethylbenzene	100-41-4	<0.3
Phenol, 2,6-Bis(1,1-Dimethyl)-	128-39-2	<0.2
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	<0.15

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
Inhalation	Remove person to fresh air and keep comfortable for breathing.
Ingestion	Immediately call a poison center or doctor/physician. Rinse mouth. Do NOT induce vomiting.

Most important symptoms and effects

SymptomsMay be harmful if swallowed. May be harmful in contact with skin. Causes serious eye
irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

, , ,

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use CO2, dry chemical, or foam for extinction.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsUse personal protective equipment as required.Environmental precautionsSee Section 12 for additional Ecological Information.Methods and material for containmentand cleaning upMethods for ContainmentPrevent further leakage or spillage if safe to do so.Methods for Clean-UpKeep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Keep cool.
onditions for safe storage, includ	ing any incompatibilities

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Kerosene 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S*	-	TWA: 100 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Refer to 29 CFR 1910.133 for eye and face protection regulations.	
Skin and Body Protection	Refer to 29 CFR 1910.138 for appropriate skin and body protection.	
Respiratory Protection	Refer to 29 CFR 1910.134 for respiratory protection requirements.	
General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice		

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Liquid Dark green (may be special blended to dark red) liquid Dark green (may be special blended to dark red)		Alcohol-type Not determined
Property_	<u>Values</u>	Remarks • Method	
рН	Not determined		
Melting point / freezing point	Not determined		
Boiling Point / Boiling Range	82.2 °C / 180 °F	ASTM D-86	
Flash Point	12.8 °C / 55 °F	ASTM D-56	
Evaporation Rate	Not determined		
Flammability (Solid, Gas) Flammability Limit in Air	Liquid-Not applicable		
Upper Flammability Limit	Not determined		
Lower Flammability Limit	Not determined		
Vapor Pressure	1.86 PSI	ASTM D-5191	
Vapor Density	Not determined		
Relative Density	0.7914	at 15.6°C (60°F) ASTM [D-1298
Water Solubility	Partial in water		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Autoignition temperature	Not determined		
Decomposition Temperature	Not determined 1.6540 cSt	ASTM D-445	
Kinematic Viscosity	Not determined	ASTM D-445	
Dynamic Viscosity Explosive Properties	Not determined		
Oxidizing Properties	Not determined		
Oxidizing i roperties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

Avoid contact with eyes.

Skin Contact May be harmful in contact with skin.

Inhalation Do not inhale.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat)4 h
Kerosene 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m³ (Rat)4 h
Naphthalene 91-20-3	= 1110 mg/kg (Rat)= 490 mg/kg (Rat)	> 20 g/kg (Rabbit)= 1120 mg/kg (Rabbit)	> 340 mg/m³ (Rat)1 h
Proprietary Organic Compound	= 26100 mg/kg (Rat)> 21500 µL/kg (Rat)	> 10 mL/kg (Rabbit)	-
Petroleum distillates, hydrotreated light naphthenic 64742-53-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2180 mg/m³ (Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Phenol, 2,6-Bis(1,1-Dimethyl)- 128-39-2	> 5000 mg/kg (Rat)	> 10 g/kg (Rabbit)	-
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	> 15 g/kg (Rat)	> 5000 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Carcinogenicity

Suspected of causing cancer. This product contains mineral oils which are considered to be severely refined and not carcinogenic under IARC. All of the mineral oils in this product contain less than 3% extractables by IP 346.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl Alcohol 67-63-0		Group 3		Х
Kerosene 8008-20-6	A3	Group 3		
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Ethylbenzene 100-41-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans NTP (National Toxicology Program) Known - Known Carcinogen Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

STOT - single exposure	May cause drowsiness or dizziness.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)3,220.20 mg/kgATEmix (inhalation-gas)734.60 mg/LATEmix (inhalation-dust/mist)5.39 mg/L	ATEmix (oral)	2,252.20 mg/kg
	ATEmix (dermal)	3,220.20 mg/kg
ATEmix (inhalation-dust/mist) 5.39 mg/L	ATEmix (inhalation-gas)	734.60 mg/L
	ATEmix (inhalation-dust/mist)	5.39 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Isopropyl Alcohol 67-63-0	1000: 72 h Desmodesmus subspicatus mg/L EC50 1000: 96 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
Naphtha (petroleum), heavy aromatic 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	 41: 96 h Pimephales promelas mg/L LC50 19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 45: 96 h Pimephales promelas mg/L LC50 flow-through 1740: 96 h Lepomis macrochirus mg/L LC50 static 	0.95: 48 h Daphnia magna mg/L EC50
Naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	31.0265: 96 h Lepomis macrochirus mg/L LC50 static 5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.99: 96 h Pimephales promelas mg/L LC50 static 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static	1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static 2.16: 48 h Daphnia magna mg/L LC50
Proprietary Organic Compound		300: 96 h Lepomis macrochirus mg/L LC50 static 0.0109: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.1: 96 h Lepomis macrochirus mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 94.5 - 271: 96 h Oncorhynchus mykiss mg/L LC50 static	102: 24 h Daphnia magna mg/L EC50
Petroleum distillates, hydrotreated light naphthenic 64742-53-6		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Ethylbenzene 100-41-4	438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Phenol, 2,6-Bis(1,1-Dimethyl)-			0.45: 48 h Daphnia magna mg/L
128-39-2			EC50
Petroleum distillates, hydrotreated		5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L
heavy paraffinic		mg/L LC50	ÉC50
64742-54-7		-	

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

<u>Mobility</u>

Chemical Name	Partition Coefficient
Isopropyl Alcohol	0.05
67-63-0	
Naphtha (petroleum), heavy aromatic	2.9 - 6.1
64742-94-5	
Naphthalene	3.6
91-20-3	
Proprietary Organic Compound	>6
Ethylbenzene	3.2
100-41-4	

Other Adverse Effects Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene	U165	Included in waste streams:		U165
91-20-3		F024, F025, F034, F039,		
		K001, K035, K060, K087,		
		K145		
Ethylbenzene		Included in waste stream:		
100-41-4		F039		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical	
			catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Isopropyl Alcohol	Toxic
67-63-0	Ignitable
Naphthalene	Toxic
91-20-3	
Ethylbenzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

<u>Note</u>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
<u>DOT</u> UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1993 Flammable liquid, n.o.s. (Isopropanol) 3 II
<u>IATA</u> UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1993 Flammable liquid, n.o.s. (isopropanol) 3 II
IMDG UN/ID No Proper Shipping Name Hazard Class Packing Group Marine Pollutant	UN1993 Flammable liquid, n.o.s. (isopropanol) 3 II This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Isopropyl Alcohol	Х	Х	Х	Х	Х	Х	Х	Х
Kerosene	Х	Х	Х		Х	Х	Х	Х

MP-016 - Fuel Treatment FT-10™

Naphtha (petroleum), heavy aromatic	Х	Х	Х		Х	Х	Х	Х
Naphthalene	Х	Х	Х	Х	Х	Х	Х	Х
Proprietary Organic Compound	Х	Х	Х	Х	Х	Х	Х	Х
Petroleum distillates, hydrotreated light naphthenic	Х	Х	Х		Х	X	Х	х
Zinc alkyl dithiophosphate	Х	Х		Х	Х			Х
Ethylbenzene	Х	Х	Х	Х	Х	Х	Х	Х
Phenol, 2,6-Bis(1,1-Dimethyl)-	Х	Х	Х	Х	Х	Х	Х	Х
Petroleum distillates, hydrotreated heavy paraffinic	Х	Х	Х	X	Х	X	Х	х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Naphthalene	100 lb 1 lb		RQ 100 lb final RQ
91-20-3			RQ 45.4 kg final RQ RQ 1 lb final
			RQ
			RQ 0.454 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Isopropyl Alcohol - 67-63-0	67-63-0	60-70	1.0
Naphthalene - 91-20-3	91-20-3	<5	0.1
Zinc alkyl dithiophosphate - 113706-15-3	113706-15-3	<0.4	1.0
Ethylbenzene - 100-41-4	100-41-4	<0.3	0.1

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene	100 lb	Х	Х	Х
Ethylbenzene	1000 lb	Х	Х	Х

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65		
Naphthalene - 91-20-3	Carcinogen		
Ethylbenzene - 100-41-4	Carcinogen		

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Isopropyl Alcohol 67-63-0	X	X	X
Kerosene 8008-20-6	Х	X	Х
Naphthalene 91-20-3	Х	X	Х
Proprietary Organic Compound		X	
Petroleum distillates, hydrotreated light naphthenic 64742-53-6		X	
Zinc alkyl dithiophosphate 113706-15-3	Х		Х
Ethylbenzene 100-41-4	Х	X	Х

16. OTHER INFORMATION

<u>NFPA</u> HMIS	Health Hazards 2 Health Hazards Not determined	Flammability 3 Flammability Not determined	Instability 0 Physical hazards Not determined	Special Hazards None Personal Protection Not determined

11-Jul-2018
13-Jul-2018
New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet