



### Muscle Hybrid Engine Treatment™

*Designed specifically for today's hybrid and low-viscosity oil engines... engineered to treat the metal...not the oil... for reduced friction and wear and enhanced engine performance*

#### Key Features & Benefits

- Protects metal surfaces of internal, moving metal parts, i.e. bearings, pistons, cam, crankshaft, lifters
- Reduces friction-related heat and wear
- Enhances engine performance and efficiency
- Lowers operating temperatures
- Reduces oil consumption
- Increases horsepower
- Improves fuel economy
- Reduces maintenance
- **Treats the metal – not the oil** – even during dry start
- Will not build up or change tolerances

#### Typical Applications

- Recommended for hybrid engines and engines that utilize low viscosity, fuel-saving motor oils.

#### Directions for Use

- Add 8 oz. to 4 to 6 quarts of low viscosity oil in crankcase every oil change. For larger engine oil reserves, add 2 oz. per each quart of oil.

#### Technical Data

Appearance .....	Dark brown liquid
Odor .....	Mild petroleum
Freezing point .....	-22°C (- 7.6°F) D2386
Initial boiling point .....	95°C (203°F) D86
Flash point .....	130°C (266°F) D93
Autoignition Temperature ....	268°C (514.4°F) E659
Vapor pressure @ 25°C .....	4.0 mm Hg D2879
VOC, wt fraction.....	0.1376 m/m EPA24
Density @ 15.5°C .....	0.9130 g/ml D4052
Lbs per gal (U.S.) .....	~ 7.619
Solubility .....	Insoluble (water)
Viscosity @ 40°C.....	14.81 cSt D445
Viscosity @ 100°C.....	3.52 cSt D445
Coefficient of friction .....	0.0980
Four-ball EP properties, LWI .....	126 D2783
Four-ball EP, Weld point, Kg .....	620 D2783

*The above properties are typical values and do not constitute a product specification.*

#### Container Availability

Item HYBRID-8.....	8-oz. bottle (236 mL)
Item HYBRID-5G .....	37 lb pail (16.8 kg)
Item HYBRID-55G .....	410 lb drum (186 kg)

© 2019-2024 Muscle Products Corp. r1.0



### MUSCLE PRODUCTS CORP.

Additives and Lubricants Engineered for Performance

752 Kilgore Road | Jackson Center, PA 16133 USA | 814-786-0166 | musclelubricants.com

Registered:  
ISO 9001