



Air Tool Oil AT-10™

Multi-functional air tool oil that lubricates, cleans and protects - Improves tool power, speed, operation and reliability

Key Features & Benefits

- Lubricates, cleans and protects
- Stops and inhibits rust
- Repels air line moisture and water spray
- Removes gummy deposits
- Improves tool performance
- Provides smoother operation
- Extends tool life
- Reduces maintenance and replacement costs
- Contains **Muscle Metal Treatment MT-10®** technology for increased lubricity and boundary film lubrication

Typical Applications

Recommended for all piston- and rotary-type air tools, such as:

- Impact and ratchet wrenches
- Nailers and staplers
- Hammers
- Sanders, grinders, and polishers
- Shears
- Drills and screw drivers
- Chisels
- Saws
- Paving breakers
- Riveters
- Tampers
- Rock drills

Directions for Use

Shake container or mix contents lightly. Use according to air tool manufacturer's instructions. Tools may need lubricated daily, or several times a day, depending on usage frequency.

NOTE: All petroleum oils have a tendency to cause **natural rubber** O-rings to swell. Before using AT-10™, check with the tool manufacturer to make sure your air tools utilize **quality, non-rubber (i.e. neoprene)** O-rings.

Technical Data

Appearance.....	Red low-viscosity liquid
Odor.....	Mild petroleum, hint of cinnamon
Boiling point	> 450°F (232°C)
Autoignition temperature	469°F (243°C)
Flash point	282°F (139°C) D-93
Specific gravity @ 60°F, g/cm ³	0.945
API gravity @ 60°F	18.2
Lbs per gal (U.S.).....	~ 7.88
Vapor pressure.....	< 0.810 psi
Viscosity @ 40°C	25.05 cSt D-445
Viscosity @ 100°C	3.90 cSt D-445
Pour point.....	< - 50°F (- 45.6°C)
Solubility.....	Insoluble (water)

The above properties are typical values and do not constitute a product specification.

Container Availability

Item AT-10-4	4 oz. bottle (118 mL)
Item AT-10-16	16 oz. bottle (473 mL)
Item AT-10-128	1 U.S. gallon (3.7 L)
Item AT-10-5G	5 U.S. gallon (18.9 L)
Item AT-10-55G	55 U.S. gallon (208 L)

