



Air Tool Oil AT-10™

Multi-functional air tool oil that lubricates, cleans and protects - Improves tool power, speed, operation and reliability

Key Features & Benefits

- Lubricates, cleans and protects
- Stops and inhibits rust
- Repels air line moisture and water spray
- Removes gummy deposits
- Improves tool performance
- Provides smoother operation
- Extends tool life
- Reduces maintenance and replacement costs
- Contains **Muscle Metal Treatment MT-10®** technology for increased lubricity and boundary film lubrication

Typical Applications

Recommended for all piston- and rotary-type air tools, such as:

- Impact and ratchet wrenches
- Nailers and staplers
- Sanders, grinders and polishers
- Paving breakers
- Screw drivers
- Hammers
- Shears
- Drills
- Chisels
- Saws
- Riveters
- Tampers
- Rock drills

Directions for Use

Shake container or mix product lightly. Use according to air tool manufacturer's instructions. Tools may need lubricated daily, or several times a day, depending on their frequency of use.

NOTE: All petroleum oils have a tendency to cause *natural rubber* O-rings to swell. Before using AT-10™, check with the tool manufacturer to make sure your air tools utilize *quality, non-rubber* (i.e. Neoprene, Buna-N, Viton, etc.) O-rings.

Technical Data

Appearance.....	Red liquid
Odor.....	Mild petroleum, hint of cinnamon
Boiling point.....	409°F (209°C)
Autoignition temperature.....	469°F (243°C)
Flash point.....	282°F (139°C) D93
Density @ 15°C, g/cm ³	0.9558
API gravity @ 60°F.....	18.2
Lbs per gal (U.S.).....	~ 7.977
Vapor pressure.....	< 0.810 PSI
Viscosity @ 40°C.....	26.4 cSt D-445
Viscosity @ 100°C.....	4.45 cSt D-445
Pour point.....	- 38°F (- 39°C)
Solubility.....	Insoluble (water)

The above properties are typical values and do not constitute a product specification.

Container Availability

Item AT-10-4.....	4 oz. bottle (118 mL)
Item AT-10-16.....	16 oz. bottle (473 mL)
Item AT-10-5G.....	38 lbs net wt / pail
Item AT-10-55G.....	430 lbs net wt / drum

