Safety Data Sheet

Issue Date: 11-Jul-2018 **Revision Date:** 13-Jul-2018 **Version** 1

1. IDENTIFICATION

Product Identifier

Product Name Throat 'n Throttle TNT-10™

Other means of identification

SDS # MP-010.2

UN/ID No UN1993

Recommended use of the chemical and restrictions on use

Recommended Use Cleans intake manifold, combustion chamber, throttle plates and valves of gasoline engines through the vacuum system.

Details of the supplier of the safety data sheet

Manufacturer Address
Muscle Products Corp
752 Kilgore Road
Jackson Center, PA 16133
www.musclelubricants.com

Emergency Telephone Number

Company Phone Number 1-814-786-0166
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear, blue liquid **Physical state** Liquid **Odor** Petroleum solvent/ alcohol

Classification

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

Signal Word
Danger

Hazard statements
Causes serious eye irritation
Suspected of causing cancer
May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response
If exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting
IN CASE OF FIRE: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other hazards
Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Stoddard solvent	8052-41-3	40-50
Isopropyl Alcohol	67-63-0	20-30
Kerosene	8008-20-6	20-30
Proprietary Organic Compound	Proprietary	4-5
N-Nonane	111-84-2	0.4-3
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	1-2
Aromatic petroleum hydrocarbons	25551-13-7	0-1.75
Naphthalene	91-20-3	<1
Ethylbenzene	100-41-4	<0.3

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice If exposed or concerned: Get medical advice/attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

Inhalation Remove person to fresh air and keep comfortable for breathing.

Ingestion Immediately call a poison center or doctor/physician. Rinse mouth. Do NOT induce vomiting.

Most important symptoms and effects

Symptoms May be harmful if swallowed. May be harmful in contact with skin. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Use CO2, dry chemical, or foam for extinction.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical
Highly flammable liquid and vapor.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Store in a well-ventilated place. Keep containers tightly closed.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m^3 (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m^3	IDLH: 20000 mg/m^3 Ceiling: 1800 mg/m^3 15 min TWA: 350 mg/m^3
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m^3 (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m^3 (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m^3	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m^3 STEL: 500 ppm STEL: 1225 mg/m^3
Kerosene 8008-20-6	TWA: 200 mg/m^3 total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S*	-	TWA: 100 mg/m^3
N-Nonane 111-84-2	TWA: 200 ppm	(vacated) TWA: 200 ppm (vacated) TWA: 1050 mg/m^3	TWA: 200 ppm TWA: 1050 mg/m^3
Aromatic petroleum hydrocarbons 25551-13-7	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m^3	-
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m^3 (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m^3 (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m^3	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m^3 STEL: 15 ppm STEL: 75 mg/m^3
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m^3 (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m^3 (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m^3	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m^3 STEL: 125 ppm STEL: 545 mg/m^3

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	Clear, blue liquid	**Odor**	Petroleum solvent/ alcohol
Color	Blue	**Odor Threshold**	Not determined

Property	**Values**	**Remarks • Method**
pH	Not determined	
Melting point / freezing point	-37 °C / -34.6 °F	ASTM D-2386
Boiling Point / Boiling Range	82.2 °C / 180 °F	ASTM D-86
Flash Point	22 °C / 71.6 °F	ASTM D-93
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Liquid-Not applicable	
Flammability Limit in Air		
Upper Flammability Limit	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	1.75 kPa	ASTM D-5191
Vapor Density	Not determined	
Relative Density	0.7923 g/cm3	at 15.6°C (60°F) ASTM D-1298
Water Solubility	Partial in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	1.27 cSt	@ 40°C (104°F) ASTM D-445
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical Stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Conditions to Avoid
Keep out of reach of children.

Incompatible Materials
None known based on information supplied.

Hazardous Decomposition Products
None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact May be harmful in contact with skin.

Inhalation Do not inhale.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m^3 (Rat) 4 h
Kerosene 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Proprietary Organic Compound	= 26100 mg/kg (Rat) > 21500 µL/kg (Rat)	> 10 mL/kg (Rabbit)	-
N-Nonane 111-84-2	-	-	= 3200 ppm (Rat) 4 h
Petroleum distillates, hydrotreated light naphthenic 64742-53-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2180 mg/m^3 (Rat) 4 h
Aromatic petroleum hydrocarbons 25551-13-7	= 8970 mg/kg (Rat)	-	-
Naphthalene 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	> 20 g/kg (Rabbit) = 1120 mg/kg (Rabbit)	> 340 mg/m^3 (Rat) 1 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Proprietary Ingredient	= 40 g/kg (Rat)	> 20 mL/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye irritation Causes serious eye irritation.

Carcinogenicity Suspected of causing cancer. This product contains mineral oils which are considered to be severely refined and not carcinogenic under IARC. All of the mineral oils in this product contain less than 3% extractables by IP 346.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl Alcohol 67-63-0		Group 3		X
Kerosene 8008-20-6	A3	Group 3		
Petroleum distillates, hydrotreated light naphthenic 64742-53-6	A2	Group 1	Known	X

Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Ethylbenzene 100-41-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 IARC components are "not classifiable as human carcinogens"
NTP (National Toxicology Program)
Known - Known Carcinogen
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2,398.30 mg/kg
ATEmix (dermal) 2,766.50 mg/kg
ATEmix (inhalation-gas) 550.40 mg/L
ATEmix (inhalation-dust/mist) 21.74 mg/L
ATEmix (inhalation-vapor) 559.51 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Isopropyl Alcohol 67-63-0	1000: 72 h Desmodesmus subspicatus mg/L EC50 1000: 96 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
Proprietary Organic Compound		300: 96 h Lepomis macrochirus mg/L LC50 static 0.0109: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.1: 96 h Lepomis macrochirus mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 94.5 - 271: 96 h Oncorhynchus mykiss mg/L LC50 static	102: 24 h Daphnia magna mg/L EC50
Petroleum distillates, hydrotreated light naphthenic 64742-53-6		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Aromatic petroleum hydrocarbons 25551-13-7		7.72: 96 h Pimephales promelas mg/L LC50 flow-through	
Naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	31.0265: 96 h Lepomis macrochirus mg/L LC50 static 5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.99: 96 h Pimephales promelas mg/L LC50 static 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static	1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static 2.16: 48 h Daphnia magna mg/L LC50

Ethylbenzene 100-41-4	438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	9.6: 96 h Poecilia reticulata mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Proprietary Ingredient	8: 72 h Desmodesmus subspicatus mg/L EC50	900: 48 h Leuciscus idus mg/L LC50	100: 24 h Daphnia magna mg/L EC50

Persistence/Degradability
Not determined.

Bioaccumulation
Not determined.

Mobility

Chemical Name	Partition Coefficient
Isopropyl Alcohol 67-63-0	0.05
Proprietary Organic Compound	>6
Naphthalene 91-20-3	3.6
Ethylbenzene 100-41-4	3.2

Other Adverse Effects
Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165
Ethylbenzene 100-41-4		Included in waste stream: F039		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain	

			chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Isopropyl Alcohol 67-63-0	Toxic Ignitable
Naphthalene 91-20-3	Toxic
Ethylbenzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1993
Proper Shipping Name Flammable liquid, n.o.s. (Isopropanol)
Hazard Class 3
Packing Group II

IATA

UN/ID No UN1993
Proper Shipping Name Flammable liquid, n.o.s. (Isopropanol)
Hazard Class 3
Packing Group II

IMDG

UN/ID No UN1993
Proper Shipping Name Flammable liquid, n.o.s. (Isopropanol)
Hazard Class 3
Packing Group II
Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Stoddard solvent	X	X	X		X	X	X	X
Isopropyl Alcohol	X	X	X	X	X	X	X	X
Kerosene	X	X	X		X	X	X	X
Proprietary Organic Compound	X	X	X	X	X	X	X	X
N-Nonane	X	X	X	X	X	X	X	X
Petroleum distillates, hydrotreated light naphthenic	X	X	X		X	X	X	X

Aromatic petroleum hydrocarbons	X	X	X	X	X	X	X	X
Naphthalene	X	X	X	X	X	X	X	X
Ethylbenzene	X	X	X	X	X	X	X	X
Proprietary Ingredient	X	X	X		X	X	X	X

Legend:

TSCA *- United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL *- Canadian Domestic Substances List/Non-Domestic Substances List*

EINECS/ELINCS *- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

ENCS *- Japan Existing and New Chemical Substances*

IECSC *- China Inventory of Existing Chemical Substances*

KECL *- Korean Existing and Evaluated Chemical Substances*

PICCS *- Philippines Inventory of Chemicals and Chemical Substances*

AICS *- Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Naphthalene 91-20-3	100 lb 1 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Isopropyl Alcohol - 67-63-0	67-63-0	20-30	1.0
Naphthalene - 91-20-3	91-20-3	<1	0.1
Ethylbenzene - 100-41-4	100-41-4	<0.3	0.1

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene	100 lb	X	X	X
Ethylbenzene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Stoddard solvent 8052-41-3	X	X	X
Isopropyl Alcohol 67-63-0	X	X	X
Kerosene 8008-20-6	X	X	X
N-Nonane 111-84-2	X	X	X

Petroleum distillates, hydrotreated light naphthenic 64742-53-6		X	
Aromatic petroleum hydrocarbons 25551-13-7	X	X	X
Naphthalene 91-20-3	X	X	X
Ethylbenzene 100-41-4	X	X	X

16. OTHER INFORMATION

NFPA	**Health Hazards**	**Flammability**	**Instability**	**Special Hazards**
	2	3	0	Not determined
HMIS	**Health Hazards**	**Flammability**	**Physical hazards**	**Personal Protection**
	Not determined	Not determined	Not determined	Not determined

Issue Date: 11-Jul-2018
Revision Date: 13-Jul-2018
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet