



Diesel High Performance DHP-10™

A must-have, new generation, multi-function diesel fuel additive formulated to increase cetane and drastically improve diesel fuel lubricity, fuel system cleanliness and performance and fuel economy

Key Features & Benefits

- Improves lubricity for improved fuel system performance
- Boosts cetane number* for quicker starts and improved fuel performance
- Concentrated formula designed to improve the quality characteristics of diesel fuel
- Reduces downtime and maintenance
- Clean injectors for optimal performance
- Protects fuel pump and injectors from wear and premature failure
- Controls injector deposit formation allowing continuous fuel flow
- Improves durability of pump and injectors
- Reduces friction during metal-to-metal contact, reducing wear on treated metal parts
- Lubricates, cleans and protects entire fuel system
- Effective steel corrosion elimination in treated fuel
- Excellent performance in new common rail direct injection systems and nozzle cleanliness in older engines
- Will not change sulfur ratings at recommended dose rate
- Contains **Muscle Metal Treatment MT-10®** technology for improved lubrication

** Independent laboratory testing showed a **6% increase** in cetane value (ASTM D-613).*

Typical Applications

- **Fuel additive:** #1 diesel, #2 diesel, and ultra-low sulfur diesel (ULSD) fuels

Directions for Use

Shake container / mix contents well before use. Add **DHP-10™** to fuel tank prior to refueling. **DHP-10™** will blend easily with the fuel during fill up.

Treat rate: 2 oz. to every 10 gallons of diesel fuel.

Technical Data

Appearance.....	Clear, amber liquid
Odor	Strong petroleum
Cloud point	- 64°C (- 82.2°F) D-2500
Pour point	< - 60°C (- 76°F) D-97
Initial boiling point	82.2°C (179.9°F) D-86
Flash point	~ 22.2°C (72°F) closed cup
Density @ 15.5°C	0.8387 g/ml D-4052
Lbs per gal (U.S.)	~ 6.999
Solubility	Partial (water); % N/D
Viscosity @ 40°C	1.47 cSt D-445
Vapor pressure @ 20°C	0.58 psi D-6378
Base number	10.44 mg KOH/g D-664A

The above properties are typical values and do not constitute a product specification.

NOTE: Low flash point. Use caution when handling this material. See SDS before use.

Container Availability

Item DHP-10-16	16 oz. bottle (473 mL)
Item DHP-10-128	1 U.S. gallon (3.7 L)
Item DHP-10-5G	5 U.S. gallon (18.9 L)
Item DHP-10-55G	55 U.S. gallon (208 L)

